

KLS-400/800

Design



H.264

Compact

CMS

Key Feature

- 4CIF real-time DVR
- Mobile application program
- Easy backup in AVI format
- Built-in Web server
- Dual-streaming for network
- Dedicated DDNS server operation (acecctv.net)
- Private masking for privacy
- PTZ control port (RS-485)
- Alarm In/Out port (RS-485)
- Easy digital zooming in both live & playback video.
- Remote system configuration in IE

Rear Design



KLS-400



KLS-800

Technical Specifications

Model		KLS-400	KLS-800
INPUT	Video(BNC)	4	8
	AUDIO(RCA)	1	1
	Alarm	1	1
OUTPUT	Video(SPOT)	1	1
	AUDIO(RCA)	1	1
	VGA	1	1
	Alarm(Relay)	1	1
PORT	USB	2	2
	PTZ(RS-485)	1	1
	Ethernet	1	1
Live	Resolution	NTSC - 720*480, PAL - 720 * 576	
	Digital Zoom	Yes	Yes
	Display	1,4	1,4,9
Recording	Resolution	NTSC - 720*480, PAL - 720 * 576	
	Frame 360*240 (360*288)	120 (100)	240 (200)
	Frame 720*240 (720*288)	120 (100)	120 (100)
	Frame 720*480 (720*576)	60 (50)	60 (50)
	Water Mark	Yes	Yes
	Rerecording	Yes	
	Post Recording	Yes	
Record Mode	Manual/Continuous/Schedule/Motion/Sensor		
Net work	Mobile View	Mobiles possible to connect Internet.	
	Interface	Static/DHCP/DDNS	
	Web Monitoring	Live/Playback/Audio/PTZ/Snapshot	
	Dual Stream	Yes	
	uPNP (Auto-Port Forwarding)	Yes	
	Bandwidth adjustable	Yes	
PTZ	Protocol	Pelco-D,P, Others	
	Preset Control	0	0
Alarm	Sensor Input	Two status : NC/No	
	Motion Detection	Selected Area, sensitivity in each channel	
	Output option	Motion detected, Alarm input detected	
	Others	Email /FTP notification, Detection of HDD Temp	
HDD	Internal	1	1
	Capacity	2 TB	2 TB
System	OS	Linux	
	Compression	H.264	H.264
	Menu	Graphic User Interface	
	Control	USB Mouse, Remote Controller, Keyboard	
	Config Load/ Save	0	0
	Time	Auto Time Sync through Time servor	
	Saving function	Day light saving function	
Firmware Upgrade	USB flash memory, NETWORK		
Log View	System operation status		